



OF
CONSTRUCTION PROJECT:

Note: The information and assembly sequences are based on our experience to the best of our knowledge and belief, but must be adapted to the on-site construction site conditions. The information is provided without guarantee. The extent to which the texts can be taken over into the tender unchanged must be checked in each individual case. The described texts are only suggestions for the tender, and mainly contain the positions in which ARDEX products are used. This specification, which has been produced by ARDEX, is not a substitute for the planning responsibility of architects and structural engineers. The completeness of the specification must be checked with regard to all of the items which are relevant and required.

The work must be carried out in accordance with the technical guidelines of ARDEX GmbH, 58453 Witten, www.pandomo.de, taking the relevant standards, regulations and trade rules into consideration in accordance with the current state of the art.

Table of contents

1	Construction site equipment.....	2
2	Samples.....	3
3	Substrate preparation.....	4
3.1	Wall and ceiling substrate preparation.....	4
4	Application.....	5
5	Surface treatment.....	6
5.1	Polishing/sanding the surface.....	6
5.2	Impregnating the surface.....	7
5.3	Sealing the surface.....	8
5.4	Maintenance of the surface.....	9
5.5	Permanently elastic sealing.....	10
6	Specialist worker hours / additional effort.....	11

General information concerning mineral filler

1. Used products:

The bidder must enclose technical data sheets and product data sheets with the bid for all products which are used or consumed in order to manufacture the mineral filler.

Failure to submit the technical data sheets with the bid will result in exclusion from the submission and the bid will not be evaluated.

2. System products:

All products which are used will be purchased from a manufacturer with a system guarantee. This also includes impregnation materials, sealing materials and surface protection. Only materials in original containers which have been standardised and approved or proof of quality testing can be provided in the form of a certificate that is accepted in Germany may be used and installed.

3. Basics:

The generally recognised rules of technology which apply in the country of implementation as well as the latest versions of the provisions, ordinances, European and national standards, regulations, directives, leaflets etc. must be adopted as the basis for the quote, the described work and the implementation of this work.

Reference is particularly made to the "Mineral decorative filler floors" leaflet issued by BSR e.V. in Bonn (May 2013). The proof of legitimacy must be provided by presenting a valid partnership agreement. In accordance with the authorisation, the bidder is entitled to process the products for which he has attended license training.

4. Evaluation:

The presented work list will be used for the quote. Only a fully completed work list can be taken into consideration during the evaluation of the quote. Alternative suggestions in the form of secondary quotes are not permitted.

5. References:

Comparable reference in picture form and a description shall be presented for the implementation of the work. On-site deadlines will also be made possible.

6. Cleaning and care concept:

The cleaning and care instructions made available on the Internet by the manufacturer of the floor covering or enclosed with the quote is regarded as binding for the user. This must be coordinated with the respective use of the project.

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
----------	-------------	----------	-------	----	----

1	Construction site equipment				
---	------------------------------------	--	--	--	--

1.1	General construction site set-up				
-----	---	--	--	--	--

Set-up of construction site for all work listed in the specification. All equipment which is needed to carry out the work must be taken account of. The construction site set-up also includes all of the necessary protective measures for adhering to the accident prevention regulations and measures for your own work.

		0	Pc
--	--	---	----	-------	-------

		1	Construction site set-up
--	--	---	--------------------------	-------	-------

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
2	Samples				
2.1	Production of sample sections				
	Manufacture of sample sections in 60x80cm format, colour and structure in accordance with the client's specification.				
		0	Pc
				2 Samples	<u>.....</u>

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
3	Substrate preparation				
3.1	Wall and ceiling substrate preparation				
3.1.1	Removal of dust and dirt				
	Removal of dust and dirt from the substrate and all loose parts and production of a load-bearing substrate. The manufacturer's technical directives must be observed.	0	m ²
3.1.2	Applying a renovation filler				
	ARDEX R 1 renovation filler on wall / ceiling Apply to wall/ceiling surfaces, solid, load-bearing and separating material free, with a coat thickness of please enter mm, max. 10 mm. The manufacturer's technical directives must be observed.	0	m ²
3.1.3	Applying a primer ARDEX P51 or PANDOMO® Primer				
	Application of the primer with ARDEX P51 or PANDOMO® Primer in a mixing ratio of 1:2 or 1:1 (depending on the absorbency of the substrate) on the cleaned substrate in one operation: Apply ARDEX P51 or PANDOMO® Primer by means of a short-pile roller and wait for it to dry. The manufacturer's technical directives must be observed.	0	m ²
3.1.4	Alternative position group 1, variant 1 Applying a primer ARDEX P4				
	Application of the primer with ARDEX P4 on the cleaned substrate in one work operation: Apply ARDEX P4 using a short-pile roller and wait for it to dry. The manufacturer's technical directives must be observed.	0	m ²	E-price only
	3.1 Wall and ceiling substrate preparation			
	3 Substrate preparation			

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
----------	-------------	----------	-------	----	----

4 Application

4.1 Filling with PANDOMO® Wall white

Production of a filling with PANDOMO® Wall white in colour **please enter** in accordance with PANDOMO® decorative smoothing compound, with a coating thickness of at least 1 mm on a prepared substrate.

Properties:

- For the design of interior wall and ceiling surfaces
- Cement-Plastic-Base
- Cures and dries quickly, without tension and cracks in all layer thicknesses
- Easy to process
- Excellent adhesion
- Very economical

The technical directives of the manufacturer of the products which are used must be observed.

0 m²
	4 Application	<u>.....</u>

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
----------	-------------	----------	-------	----	----

5 **Surface treatment**

5.1 **Polishing/sanding of the surface**

5.1.1 **Surface polishing, filler compound**

Polishing of the PANDOMO® filler compound with a suitable sanding machine (e.g. Trio from Lägler, Festool, Mirka etc.)
The manufacturer's technical directives must be observed.

0 m²

5.1 Polishing/sanding of the surface

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
----------	-------------	----------	-------	----	----

5.2 Impregnating the surface

5.2.1 PANDOMO® SP-SL

Application of two coats of oil impregnation PANDOMO® SP-SL stone oil.
The technical directives of the manufacturer of the products which are used must be observed.

0 m²

5.2 Impregnating the surface

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
5.3	Sealing the surface				
5.3.1	Priming the surface PANDOMO® Primer (1:1) diluted with water is recommended as the primer for PANDOMO® SP-PS. Applied with a microfibre roller, crosswise.	0	m ²
5.3.2	PANDOMO® SP-PS Application of PANDOMO® SP-PS polyurethane sealant in two forms. Application takes place crosswise, using a short pile roller. If no impregnation using PANDOMO® SP-SL or impregnation has been used, or the surfaces are heavily used and require a considerable amount of cleaning effort, a third application is required. The technical directives of the manufacturer of the products which are used must be observed.	0	m ²
		5.3 Sealing the surface <u>.....</u>			

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
5.4	Surface treatment				
5.4.1	Eventual position PANDOMO® SP-F pore filler Application of the PANDOMO® SP-F pore filler after approx. 12 hours of drying of the first application (not required if using PANDOMO® SP-PS). The technical directives of the manufacturer of the products which are used must be observed.	0	m²	E-price only
5.4.2	Eventual position PANDOMO® SP-GS Silk Gloss Seal Application of PANDOMO® SP-GS Silk Gloss Seal with a wipe coating. After approx. 60 minutes, application of the second coat of PANDOMO® SP-GS. The technical directives of the manufacturer of the products which are used must be observed.	0	m²	E-price only
5.4.3	Eventual position PANDOMO® SP-MS Silk Gloss Seal Application of PANDOMO® SP-MS Silk Gloss Seal with a mopping pad. After approx. 60 minutes, application of the second coat of PANDOMO® SP-MS. The technical directives of the manufacturer of the products which are used must be observed.	0	m²	E-price only
5.4 Surface treatment					<u>XXXXXXXXXXXX</u>

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
5.5	Permanently elastic sealing				
5.5.1	ARDEX SN Neutral Silicon Permanently elastic sealing with ARDEX SN neutral silicone. The manufacturer's technical directives must be observed.	0	m
5.5.2	ARDEX ST Natural Stone Silicone Manufacture of elastic joints with ARDEX ST Natural Stone Silicone in accordance with the technical regulations, width up to 10 mm.	0	m
	5.5 Permanently elastic sealing		
	5 Surface treatment		

Wall

Wall specifications

Position	Description	Quantity	Units	EP	GP
6	Specialist worker hours / additional effort				
6.1	Specialist worker hours				
	Specialist worker in accordance with proof for e.g. sampling, processing and casting defects, processing at ramps and rails etc. Materials such as: Resin, sand and casting compounds are billed for in accordance with the actual consumption in complete packages.				
		0	Hrs
6.2	Increased work effort and long transport distances				
	Surcharge for increased work effort and long transport distances.				
		0	Pc
		6	Specialist worker hours / additional effort

Summary

1	Construction site equipment
2	Samples
3.1	Wall and ceiling substrate preparation
3	Substrate preparation
4	Application
5.1	Polishing/sanding of the surface
5.2	Impregnating the surface
5.3	Sealing the surface
5.4	Surface treatment	XXXXXXXXXXXXX
5.5	Permanently elastic sealing
5	Surface treatment
6	Specialist worker hours / additional effort
	Sum total
	Plus VAT at %	<u>.....</u>
	Grand total	<u>.....</u>