



PANDOMO® TerrazzoHardener

Additive for consolidating and compacting surfaces of PANDOMO® Terrazzo Systems

- Additive based on water-dissolved silicate components
- Improves in combination with PANDOMO® TerrazzoFiller the properties regarding abrasion resistance, surface hardness, chemical resistance and impact strength
- Odourless and solvent-free



Application:

PANDOMO® TerrazzoHardener is used in the production of ground or polished PANDOMO® Terrazzo floors/systems to consolidate and compact the pore structure.

PANDOMO® Hardener hardens the PANDOMO® Terrazzo and thus leads to significantly more gloss and to improved properties regarding abrasion resistance, surface hardness, chemical resistance and impact strength.

Properties:

PANDOMO® Hardener is based on water-dissolved silicate components.

Application on PANDOMO® Terrazzo surfaces:

After sufficient drying of the PANDOMO® Terrazzo floors, the surface must be evenly sanded.

Before applying PANDOMO® TerrazzoHardener, the surface must be cleaned and slightly pre-wetted. PANDOMO® TerrazzoHardener requires water to react.

Apply PANDOMO® TerrazzoHardener generously and evenly with a weed wiper. Allow to soak in for approx. 15 minutes. Reapply PANDOMO® TerrazzoHardener to areas that have dried out. Always work wet in wet (flooding) to achieve optimum saturation of the substrate from the outset.

Island and puddle formation must be avoided. Remove too much applied material in good time before the gelling phase (hardening phase). If necessary or to increase the result, the application can be repeated after a few hours or the next day.

It is recommended to let the treated surface cure overnight before further processing.

After applying PANDOMO® TerrazzoFiller with PANDOMO® TFW or sanding dust, the procedure described above can be repeated.

After 8 hours, the surface is wet sanded.

To be noted:

Before application, the surface must be free of dust, grease, oil and other contaminants. The temperature of the floor and the ambient air must be at least 7°C.

Safety and disposal instructions:

The information in the safety data sheet must be observed.



PANDOMO® TerrazzoHardener

Additive for consolidating and compacting surfaces of PANDOMO® Terrazzo Systems

Technical data according to ARDEX quality standard:

Specific weight:	approx. 0.9 kg/l
Material requirement:	approx. 0.05 to 0.3 litres per m ²
Packing:	Canister with 20l
Storage:	in dry rooms approx. 12 months in the original sealed container storable